






TECHNICAL DATA SHEET - CST 0131/03 - 24/09/2013

## GL 7000

(*)				
T	°C	-200 +280		
p	bar		200	50
V	m/s		2	25
pH		0 + 14		



Avoid the product's use at the maximum temperature and pressure associated values without consult the manufacturer

### Composition

- ePTFEg yarns

### Features

The packing GL7000 is made by high strength ePTFE yarns filled with graphite powder and silicon lubricant.

### Applications

Packing suitable for reciprocating and centrifugal pumps. Avoid the strong oxidizers

size mm	size inch	kg/box	lbs/box	mt/box	ft/box	mt/kg	ft/lbs
3,0	1/8	1,0	2,2	69,4	228	69,4	103,4
4,0	-	1,0	2,2	39,1	128	39,1	58,2
5,0	3/16	1,0	2,2	25,0	82	25,0	37,2
6,0	-	2,5	5,5	43,4	142	17,4	25,9
6,5	1/4	2,5	5,5	37,0	121	14,8	22,0
8,0	5/16	2,5	5,5	24,4	80	9,8	14,5
9,5	3/8	2,5	5,5	17,3	57	6,9	10,3
10,0	-	2,5	5,5	15,6	51	6,3	9,3
11,0	7/16	2,5	5,5	12,9	42	5,2	7,7
12,0	-	2,5	5,5	10,9	36	4,3	6,5
12,7	1/2	2,5	5,5	9,7	32	3,9	5,8
14,0	9/16	5,0	11,0	15,9	52	3,2	4,7
16,0	5/8	5,0	11,0	12,2	40	2,4	3,6
17,5	11/16	5,0	11,0	10,2	33	2,0	3,0
18,0	-	5,0	11,0	9,6	32	1,9	2,9
19,0	3/4	5,0	11,0	8,7	28	1,7	2,6
22,0	7/8	5,0	11,0	6,5	21	1,3	1,9
25,5	1	5,0	11,0	4,8	16	1,0	1,4

Packaged +/- 10 % in weight.  
Customized sizes and packaging are available on demand